



Krupa, E., Cooper, J., Pirrera, A., & Silva, G. H. C. (2016). *Aeroelastic Tailoring for Enhanced Aerodynamic Wing Performance*. Paper presented at 5th Aircraft Structural Design Conference, Manchester, United Kingdom.

Peer reviewed version

[Link to publication record in Explore Bristol Research](#)
PDF-document

University of Bristol - Explore Bristol Research

General rights

This document is made available in accordance with publisher policies. Please cite only the published version using the reference above. Full terms of use are available:
<http://www.bristol.ac.uk/red/research-policy/pure/user-guides/ebr-terms/>

Aeroelastic Tailoring for Enhanced Aerodynamic Wing Performance

Eduardo P. Krupa¹, Jonathan E. Cooper², Alberto Pirrera³, Gustavo H.C. Silva⁴

*Department of Aerospace Engineering, University of Bristol, Queen's Building, University Walk,
Bristol BS8 1TR, UK.*

This study investigates the use of a novel aeroelastic tailoring design methodology for the optimisation of aircraft performance. An optimisation framework which integrates static and dynamic aeroelastic analyses with the optimisation of blended laminates has been developed. The framework uses an inverse design method to find the lightest composite structure that attains a desired aerodynamic shape, whilst also meeting a number of structural and aeroelastic constraints. A bi-level approach, integrating gradient-based and particle swarm optimisations, is used to tailor the wing structure at stringer bay level and to obtain feasible and detailed stacking sequences for the composite wing skin. The tailoring capabilities offered by composite materials are benchmarked in terms of aeroelastic performance by comparing optimised solutions against an all-metallic wing obtained with the same methodology. Two different design studies are performed: the first one minimises mass only. The second minimises the difference between a target aerodynamic shape and deformed wing shape in terms of local twist distributions. Optimisation design variables include: thicknesses of the metallic and composite panels; composite lamination parameters; position, orientation and spacing of stringers and ribs. Constraints on maximum allowable stresses, maximum deflections, flutter speed and buckling are considered, together with composite manufacturing guidelines. Results for multiple manoeuvres and cruise load cases are presented. It is shown that the proposed approach enables aerostructurally efficient solutions to be found using a representative civil jet aircraft wing.

Keywords: passive aeroelastic tailoring, composite optimisation, jig-shape, induced elastic twist.

¹ Ph.D. Research Student.

² Royal Academy of Engineering Airbus Sir George White Professor of Aerospace Engineering, AFAIAA.

³ Lecturer in Composite Structures, Advanced Composites Centre for Innovation & Science (ACCIS).

⁴ Embraer S.A., Av. Brigadeiro Faria Lima, 2170, 12227-901 São José dos Campos, São Paulo, Brazil